нотес	AUTOMATIC SANITARY WARE
	Automatic sensor faucet ITEM: 19.102
	COMPONENTS & MATERIALS
	·Touchless sensor faucet, surface mounted.
	·Highest durability and rusting resistance.
	·Easy install and maintenance.
	·Suitable for hotel bathrooms.
	·Saving water.
	TECHNICAL SPECIFICATIONS
	·Made of high quality brass, chrome finish.
	·DC/AC
	•Powered with 4 "AA" batteries of 1,5 V. Life: 1 year.
	(based on 200 cycles one day.)
	·Suitable water pressure: 0.05-0.6 MPa
	·Ambient temperature: 0-45 °C
	·Ambient humidity: <95%RH
	·Dia.of inlet pipe: G1/2" (DN15)
97 .	·Dia.of outlet pipe: G1/2" (DN15)
	·Degree of protection by enclosure: IP56
1 a st	·Detection zone: 6-25cm. Preset 15 cm. The date based on
	30x30 cm standard white board.
	·Equipped with fixing materials.
TECHNICAL SPECIFICATIONS	TECHNICAL DRAWING
	160mm
Power: DC/AC	
Suitable water pressure 0.05-0.6 MPa	
Degree of protection by enclosure IP56	
	175mm