

15.121.W	15.126.W	15.127.W	15.128.W	
white epoxy	white epoxy	white epoxy	white epoxy	

·Vertical swing-up grab bar with roll holder hock to place next to the wash basins and toilet.

·It consists of a "U" shape tube, a paper roll holder and aheavy-duty wall plate, 3 mm thick.

•15.127.W 15.128.W has cast iron legs, height can be adjusted by the leg covers.

•15.121.W has toilet paper hook.

·Safety swing-up position that locks the bar in vertical position.

·Made of cast iron, white epoxy. Ø32 mm tube grab, 1.2mm thickness.

 $\cdot Recommended$ for use in bathrooms and showers.

 $\cdot Suitable for bathrooms adapted to disabled.$

·Highest durability and rusting resistance.

·Other models available: 600 mm / 700 mm / 760 mm / 800 mm.

COMPONENTS & MATERIALS

TECHNICAL SPECIFICATIONS

•Ø32 mm tube grab. Steel thickness: 1,2 mm.
•Recommended installation height: 70-75 cm from floor.
•Stainless steel screws and volts for masonry walls.
•Incorporates 6 screws holes for wall mounting.
•With brake and paper holder.

Bar tube	Ø32 mm	
Bar tube thickness	1.2 mm	
Mounting flange	100x300 mm	