HOTEC

HAND DRYER

SENSOR OPERATED

JET



Reference: 11.103 white



Reference: 11.104 silver grey

COMPONENTS	& MATERIALS
COMIT ON ENTRY	& MAILMALS


- ·High-impact ABS one-piece cover.
- ·Universal brush motor incorporating a safety thermal cut-off.
- ·5 IR sensors in both sides for automatic hands detection.
- ·Filter which avoids the entry of the large particles.
- ·Internal tank to collect the water and avoid a mess.
- Designed for high traffic bathroom and continuous use.
- ·Easy maintenance.
- ·Dimension: 650 high x 292 wide x 250 deep mm.

TECHNICAL SPECIFICATIONS	
· Material	ABS
· Cover thickness	3.0 mm thick
· Voltage/Frequency	AC220V, 50/60Hz
· r.p.m.	20000
· Total power	1800W
· Motor power	750W
· Heating element power	1050W
· Air velocity	75m/s
· Air temperature	23-42℃
· Noice level	<85dB
· Protection level	IPX4
· Drying time	10-15s

CERTIFICATE

CE ROMS

TECHNICAL DRAWING



Tel: +86 571 888 685 70

hotec@cnhotec.com www.cnhotec.com

Fax: +86 571 888 685 71