HOTEC

HAND DRYER

SENSOR OPERATED

JET



Reference: 11.105

white



Reference: 11.106

silver grey

winte	white shive grey	
COMPONENTS & MATERIALS	TECHNICAL SPECIFICATIONS	
·High-impact ABS one-piece cover.	· Material	ABS
·High speed brush motor.	· Cover thickness	3.0 mm thick
·1 IR sensors on the top for automatic hands	· Voltage/Frequency	AC220V, 50/60Hz
detection.	· Consumption	5.0-8.0A
·HEPA filter which avoids the entry of the tiny	· r.p.m.	11000-22000
particles.	· Total power	1050-1450W
Internal tank to collect the water and avoid a mess.	· Motor power	900W
Designed for high traffic bathroom and continuous	· Heating element power	550W
use.	· Air velocity	90-135m/s
·Easy maintenance.	· Air temperature	20-40°C
·Dimension: 615 high x 318 wide x 185 deep mm.	· Noice level	69dB
	· Protection level	IPX4
	· Drying time	7-10s
CERTIFICATE	TECHNICAL DRAWING	
CE ROMS	615mm	

Tel: +86 571 888 685 70 hotec@cnhotec.com www.cnhotec.com

Fax: +86 571 888 685 71

_ 318mm __

- 185mm -