

# Sanitary Ware

Develop a good habit of washing hands





**19.101**

material: brass  
finish: chrome



**19.102**

material: brass  
finish: chrome



**19.103**

material: brass  
finish: chrome

**COMPONENTS & MATERIALS**

- Touchless sensor faucet, surface mounted.




batteries box

DC/AC	
Power	6V / 180 ~ 240V/50HZ
Power consumption	DC 6V. 4AA alkaline batteries lasts 1 years based on 200 cycles a day.
Detection zone	6-25 cm. Preset 15 cm.


Ambient temperature	0-45°C
Ambient humidity	<95%RH
Dia. Of inlet pipe	G1/2" (DN15)
Degree of protection by enclosure	IP56

**TECHNICAL SPECIFICATIONS**


**19.101**



**19.102**



**19.103**




### 19.111

material: brass  
finish: chrome




### 19.112

material: brass  
finish: chrome



### 19.113

material: brass  
finish: chrome



#### COMPONENTS & MATERIALS

- Touchless sensor faucet, surface mounted.
- Adjustable the hot and cold water.




batteries box

DC/AC	
Power	6V / 180 ~ 240V/50HZ
Power consumption	DC 6V. 4AA alkaline batteries lasts 1 years based on 200 cycles a day.
Detection zone	6~25 cm. Preset 15 cm.


Ambient temperature	0~45°C
Ambient humidity	<95%RH
Dia. Of inlet pipe	G1/2" (DN15)
Degree of protection by enclosure	IP56

#### TECHNICAL SPECIFICATIONS


19.111



19.112



19.113





**19.114**

material: brass  
finish: chrome



**19.115**

material: AISI 304 stainless steel  
finish: chrome




**19.116**

material: AISI 304 stainless steel  
finish: chrome



**COMPONENTS & MATERIALS**

- Touchless sensor faucet, surface mounted.
- Adjustable the hot and cold water.




batteries box

DC/AC	
Power	6V / 180 ~ 240V/50HZ
Power consumption	DC 6V. 4AA alkaline batteries lasts 1 years based on 200 cycles a day.
Detection zone	6-25 cm. Preset 15 cm.


Ambient temperature	0-45°C
Ambient humidity	<95%RH
Dia. Of inlet pipe	G1/2" (DN15)
Degree of protection by enclosure	IP56

**TECHNICAL SPECIFICATIONS**


**19.114**



**19.115**



**19.116**



**19.131A**

height: 175mm  
 material: AISI 304 stainless steel  
 finish: chrome



**19.131B**

height: 235mm  
 material: AISI 304 stainless steel  
 finish: chrome

**19.131C**

height: 330mm  
 material: AISI 304 stainless steel  
 finish: chrome

**19.132**

material: AISI 304 stainless steel  
 finish: chrome



**COMPONENTS & MATERIALS**

- Touchless sensor faucet, surface mounted.




batteries box

DC/AC	
Power	6V / 180 ~ 240V/50HZ
Power consumption	DC 6V. 4AA alkaline batteries lasts 1 years based on 200 cycles a day.
Detection zone	6-25 cm. Preset 15 cm.


Ambient temperature	0-45°C
Ambient humidity	<95%RH
Dia. Of inlet pipe	G1/2" (DN15)
Degree of protection by enclosure	IP56

**TECHNICAL SPECIFICATIONS**


19.131A



19.131B



19.131C



19.132

